

\$ Saver Product Line

- ◆ Integrates LTE-800 and GSM-900 Bands
- ◆ Low PIM Guaranteed
- ◆ 50 dB Input Isolation
- ◆ 250 W/port Avg. Power
- ◆ Minimal RF Insertion Loss & Ripple
- ◆ Rugged, High Reliability, IP68
- ◆ Low Cost Design
- ◆ RoHS compliant



Model Number	Connectors	Input Power Avg.	Peak	Weight, nom. lb. (kg)
BK-55D	7-16 (f)	250W	3kW	13.2 (6.0)

Microlab BK-55D is a Diplexer which allows combination and separation of the LTE-800 and GSM-900 signals, To minimize band inter-reaction, the inputs are well isolated and have minimal insertion loss over their respective frequency bands.

The Diplexer has been designed using passive, proprietary techniques which minimizes cost and size. At the same time it ensures minimal loss and very high reliability at input powers up to 250W per input.

DC pass through connections are included in the design. (02/15)

Frequency Bands:

LTE-800 Port 1 - 3: 790-862 MHz

GSM-900 Port 2 - 3: 890-960 MHz

P1:P2 Isolation: >50 dB in band, P3 terminated

VSWR, all ports: <1.25:1

Passband Loss: <0.3 dB

Intermod. Distortion: <-155 dBc
(tested with 2 +43dBm tones)

DC Path: all paths

Surge Protection: 3kA using 10/350µs pulse

Impedance: 50Ω nominal

Environment: -40°C to +65°C, IP68

Finish: Connectors: 7-16 (f) long neck triplate

Housing: Grey Paint Coating

Mounting Kit: Included for pole diameter
2.75 - 4.35 in., 70 - 110 mm



