

- ◆ Ultra wide-band, taper design
- ◆ **Models for Outdoor Environment**
- ◆ 6, 10, 15, 20 & 30 dB Values
- ◆ Minimal RF Insertion Loss
- ◆ Low Specified PIM
- ◆ 200 Watt Average Main Line Power
- ◆ 4.1-9.5, 7-16, 4.3-10 or N Connectors
- ◆ Includes Mounting Bracket (Not shown)



The CK-10 series of Directional Couplers is a tapered strip-line design covering from 694 to 3,600 MHz. Units couple off a defined fraction of signal with minimal reflections or loss. Each model is available as a 4 port coupler.

The extremely wide frequency range allows use with multiband antennas, leaky cable systems and wireless base stations. With minimal solder joints and a low loss dielectric, the dissipative loss has been minimized and reliability enhanced. Mounting brackets are included.

Four port directional couplers are available with LC, LD, LE or LN suffix, (e.g. **CK-16LN**). For outdoor environments add suffix 'P' to Model No. (e.g. **CK-16NP**).


Frequency:	694-3600 MHz
VSWR	1.20:1 max., 694-2500 MHz 1.25:1 max., 2500-3300 MHz 1.40:1 max., 3300-3600 MHz
Intermod., PIM:	-161 dBc (2 tones at +43 dBm)
Power Rating:	200 W avg., 1.5 kW pk*
Directivity:	20 dB min., 694-2500 MHz 18 dB min., 2500-3300 MHz 16 dB min., 3300-3600 MHz
Impedance:	50Ω nominal
Environment:	0°C to +50°C, below 0°C coupling is maintained but directivity degrades
Housing Finish:	RoHS Compliant
Indoor /IP64:	Standard model, Passivated Al.
Outdoor /IP67:	Adds paint (Add P to Model No.)
Connectors:	Triplate
Weight:	7-16 DIN 26 oz, 0.75 kg, nominal 4.1-9.5, 4.3-10 & N-type 24 oz, 0.67 kg, nominal

*Power may be limited by feeding into poorly matched loads overloading the termination.

3 Port Model Numbers*				Coupling nom.	Frequency Sensitivity		Coupled Loss	Dissipative Loss, dB
4.1-9.5 [†]	7-16	N Type	4.3-10		694-2500 MHz	2500-3600 MHz		
CK-15C	CK-15D	CK-15N	CK-15E	15 dB	+1.2/-0.8 dB	+1.2/-0.8 dB	0.14 dB	<0.30
CK-16C	CK-16D	CK-16N	CK-16E	6 dB	±0.75 dB	±0.9 dB	1.26 dB	<0.30
CK-17C	CK-17D	CK-17N	CK-17E	10 dB	±1.0 dB	±1.0 dB	0.45 dB	<0.30
CK-18C	CK-18D	CK-18N	CK-18E	20 dB	±1.0 dB	±1.0 dB	0.04 dB	<0.30
CK-19C	CK-19D	CK-19N	CK-19E	30 dB	±1.0 dB	±1.2 dB	0.01 dB	<0.30

*4 Port models are available with LC, LD, LE or LN suffix. Add 'P' to Model Number for Outdoor Finish.

[†]"Mini-DIN" Connector



Note: Specifications are subject to change without prior notification.

19APR2016