

- ◆ Connects 3 inputs to 3 outputs with minimal interaction & PIM
- ◆ Just 4.8 dB coupled loss/channel
- ◆ Up to 25 dB Isolation, Low VSWR
- ◆ Low and High Wireless Bands
- ◆ 60W/input average Power Rating
- ◆ Convenient connector spacing
- ◆ RoHS compliant



Indoor Model No	Outdoor IP67 Model No	Connector (female)	Frequency Range, MHz	Isolation dB	Input VSWR	*Coupling & Variation	Weight, nom. lbs. (kg)
<b>CM-81D</b>	<b>CM-81DP</b>	7-16 mm	698 - 2,200	>25 dB	<1.20:1	5.0 ± 0.8 dB	3.4 (1.6)
			2,200 - 2,600		<1.20:1	5.3 ± 1.3 dB	
			2,600 - 2700		<1.25:1	5.3 ± 1.3 dB	
<b>CM-81N</b>	<b>CM-81NP</b>	N conn	698 - 2,200	>23 dB	<1.20:1	5.0 ± 0.8 dB	3.0 (1.4)
			2,200 - 2,700			5.3 ± 1.3 dB	

\*Coupling includes dissipative loss

A 3:3 Hybrid Combiner is a network of three hybrid couplers, which combines up to three inputs. In DAS applications, all three outputs may be used to feed different cables, essentially providing lossless combining. Any unused ports must be terminated in 50Ω at the appropriate power rating.

This network is an important building block in combining boxes used in neutral host in-building distributed antenna systems. See models in the KM series. (01/13)

Coupling, all paths: 4.8 dB nominal  
 Impedance: 50Ω nominal  
 Power Rating/input: 60W avg., 3kW pk.  
 Environment: -35° to +65°C, IP64  
 IP67 on outdoor models  
 PIM (Intermodulation): <-150 dBc (with +43 dBm x2 tones) (using low PIM loads)  
 Finish: Housing: Passivated Aluminum  
 Connectors: Triplate

