


- ◆ Extremely Rugged High Power Loads
- ◆ High Temperature Refractory Load Elements
- ◆ Economic Convection Design
- ◆ Available with most Common Flanges



Microlab WE series dummy loads are rugged high power units designed to satisfy minimum cost and weight objectives for bands from 1.12 to 40.0 GHz. The WE loads employ high temperature refractory load elements designed to meet the requirements of MIL-D-3954A. These load elements are in direct contact with the waveguide walls for optimum heat transfer. They can withstand extremely high temperature, temperature gradients and thermal shocks.

These loads can be supplied to operate over the full indicated waveguide frequency band. Generally a more economical unit can be furnished for use over narrower frequency ranges.

The table below provides power ratings for each model. The independent average power rating assumes CW operation, and the independent peak power rating assumes negligible average power. The combined average and peak power ratings should be employed together. For additional cooling fins see the WF series. (8/12)

Dissipative	
Material:	Refractory
Test Pressure:	35 psig. max.
Housing Finish:	Black Paint Per TT-E-489
Flange Type:	
<2.6 GHz:	Contact
>2.6 GHz:	Flange Cover
Material:	Aluminum
Flange Finish:	Iridite Per MIL-C-5541

Model No.	Frequency Range GHz	Waveguide Size		Power Ratings				VSWR max.	Nominal Dimensions Inches (mm)			Weight nom. lbs (kg)
		RG	WR	W avg.	kW pk.* @40 psig	W avg.	kW pk.** @30 psig		L	W	H	
WE-0005	1.12 - 1.70	103	650	2250	65,000	1500	20,000	1.15:1	32.9 (836)	6.9 (175)	8.7 (221)	67 (30.4)
WE-0015	1.70 - 2.60	105	430	1500	30,000	1000	10,000	1.15:1	21.8 (554)	6.0 (152)	6.4 (163)	21 (9.5)
WE-0025	2.60 - 3.95	75	284	1200	12,500	750	4,000	1.10:1	14.0 (356)	5.3 (135)	5.3 (135)	7.5 (3.4)
WE-0035	3.95 - 5.85	95	187	800	5,250	500	1,800	1.10:1	9.8 (249)	3.7 (94)	3.7 (94)	3.9 (1.8)
WE-0045	5.85 - 8.20	106	137	500	2,750	300	1,000	1.10:1	7.9 (201)	3.2 (81)	3.2 (81)	2.3 (1.05)
WE-0050	7.05 - 10.0	68	112	300	1,750	175	750	1.10:1	6.3 (160)	1.9 (48)	2.2 (56)	1.0 (0.45)
WE-0055	8.20 - 8.80 8.80 - 12.4	67	90	250	1,250	150	350	1.15:1 1.10:1	5.7 (145)	1.7 (43)	1.9 (48)	0.8 (0.36)
WE-0065	12.4 - 18.0	349	62	150	650	100	250	1.10:1	4.1 (104)	1.3 (33)	1.7 (43)	0.4 (0.18)
WE-0075	18.0 - 26.5	121	42	125	225	75	100	1.15:1	4.1 (104)	1.0 (25)	1.3 (33)	0.2 (8.4)
WE-0085	26.5 - 40.0	‡96	28	75	125	50	75	1.20:1	4.2 (107)	0.8 (20)	1.0 (25)	0.2 (0.09)

‡Aluminum Equivalent † see text *at pressure of 35 psig ** at pressure of 10 psig